



## ***New & Improved DYNA-PURGE® C Designed for Clear and Transparent Resins***

**DYNA-PURGE C** is a clear, non-abrasive, non-chemical engineered thermoplastic purging compound, formulated to purge high clarity resins such as PET, GPPS, PC, SAN and PMMA. A proprietary additive expands allowing for the purge to reach and clean all areas of the machine. The carrier matrix then flushes away the previous resin and other impurities, eliminating any “milky drag” or residue.

<b>Applications:</b>	<b>Injection</b> - cold and hot runners <b>Extrusion</b> - profile, sheet, compounding, blow molding
<b>Temperature Range:</b>	380° F - 590° F (193° C - 310° C)
<b>Types of Resins:</b>	PET, GPPS, PC, SAN, PMMA as well as other clear and transparent resins
<b>Minimum Clearance:</b>	None
<b>Amount of Purge:</b>	1 to 2 times barrel capacity(actual amount needed depends on machine conditions)

### **FEATURES & BENEFITS:**

- Excellent for transition to clear or transparent resin, preventative machine maintenance, and before manual cleaning
- Excellent for purging through hot runner systems, dies, or other downstream equipment
- Effective through a wide temperature range 380°F-590°F(193°C-310°C)
- Easy to use – no process adjustment necessary – use at the resident resin processing temperature and RPM speed
- Non-abrasive thermoplastic, which thoroughly loosens carbonized and degraded resin, allowing it to be flushed out of the system
- Safe, non-hazardous, with no chemicals – ingredients are FDA compliant
- Heat stable – recommended during shutdown and start-up
- Low “cost-per-purge” – only small quantity needed to be effective
- No mixing required – simply use “as is”
- Unlimited shelf life

Dyna-Purge has been the top performing purging compound for over 30 years! Our product line offers superior cleaning and economic value over in-house methods and other commercial purges. We invite you to sample Dyna-Purge at no charge, so you can prove it to yourself.

***Please refer to “Suggested Purging Procedures” for processing information and “Grade Selection Guide” regarding additional products.***

Important! The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true to the best of our knowledge. NO WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling or storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel can respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State or local laws.

Dyna-Purge® and Productivity Begins With Purging® are registered trademarks of Shuman Plastics, Inc.

35 Neoga Street • Depew, New York 14043, USA • Phone 716-685-2121 • Fax 716-685-3236 • [info@dynamapurge.com](mailto:info@dynamapurge.com) • [www.dynamapurge.com](http://www.dynamapurge.com)