

HSG-SC230-KIT

STYRO-CUTTER

DATASHEET

TYPE HSG-SC STYRO-CUT 230

The powerful performance professional tool for the Building Trade
With electronic power control,
for an optimal adjustment of the blade temperature.
For board thicknesses **up to 230mm (9.1")** and for specialty cuts.

Technical Description:

Heats up in only 10 seconds
Supply voltage: 230V-50Hz
Power input: max. **230 Watt**
Optimal level of efficiency
LED-power indicator
Protective insulation
Mains cord 3m
Blade temperature 500°C (930°F) max.
Eliminates styrofoam dust
Low Weight: 0,6 kg, 1,5 kg incl. plastic case and accessories

Basic Kit:

- 1 STYRO-CUT 230
- 2 Blades (1x DSS-220 for boards up to 200 mm and 1x DSS-250 for boards up to 230mm)
- 1 Brass brush
- 1 Screwdriver
- 1 Manual
- 1 Solid plastic case



Practicable blades:

Type DSS-200
For boards
up to 180 mm (7.1")



Type DSS-220
For boards
up to 200 mm (7.9")



Type DSS-250
For boards
up to 230 mm (9.1")



Type C-100
For boards
up to 100 mm (4")




Type C-140
For boards
up to 140 mm (5.5")



Type C-160
For boards
up to 160 mm (6.3")



Type C-180
For boards
up to 180 mm (7.1")




Type C-200
For boards
up to 200 mm (7.9")



Type C-230
For boards
up to 230 mm (9.1")



Type CN-14, curved
For 14 mm grooves



Type CN-20 curved
For 20 mm grooves




Type CN-26 curved
For 26 mm grooves



Type CR-20 curved
For 20 mm grooves
With depth guide



Type CS-20 curved
For 20 mm grooves
With depth guide



Connector socket cutter
Typ D68-61
For cutting holes Ø 68 mm

